

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 1 235 445 A1

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
28.08.2002 Bulletin 2002/35

(51) Int Cl.7: H04Q 7/32

(21) Application number: 01301345.3

(22) Date of filing: 16.02.2001

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

- Gouere, Francois
Jouars Pontchartrain 78760 (FR)
- Garcin, Thierry
Paris 75015 (FR)
- Roberts, Michael
Southend on Sea, Essex SS2 5EB (GB)

(71) Applicant: LUCENT TECHNOLOGIES INC.
Murray Hill, New Jersey 07974-0636 (US)

(74) Representative:
Buckley, Christopher Simon Thirsk et al
Lucent Technologies (UK) Ltd,
5 Mornington Road
Woodford Green, Essex IG8 0TU (GB)

(72) Inventors
• D'Herbemont, Luc
Paris 75004 (FR)

(54) User equipment device for a UMTS mobile telephone communications system

(57) The present invention relates to a user equipment device of a UMTS (Universal Mobile Telephone System) type mobile radio telecommunications system. The user equipment device (UE) works selectively in two modes of operation: a connected mode in which resources of the system are allocated to setting up a connection with the user equipment device and an idle mode. The user equipment device is identified in idle mode by a first identity (IMSI; TMSI; PTMSI) and in connected mode by a second identity. According to the invention, the user equipment device in connected mode is capable of processing messages in which it is identified by its first identity (IMSI; TMSI; PTMSI).

nection with the user equipment device and an idle mode. The user equipment device is identified in idle mode by a first identity (IMSI; TMSI; PTMSI) and in connected mode by a second identity. According to the invention, the user equipment device in connected mode is capable of processing messages in which it is identified by its first identity (IMSI; TMSI; PTMSI).




FIG.2

Description

[0001] The present invention relates to a UMTS. (Universal Mobile Telephone System) type mobile radio telecommunications system.

[0002] A UMTS type system consists of a UTRAN (Universal Terrestrial Radio Access Network) type of network, mobile terminals, commonly known as user equipment (UE) devices, and a core network connected to the public switched telephone network and the Internet. A system of this kind is illustrated in Figure 1. The UTRAN network consists of a set of radio network sub-systems RNS connected to the core network by means of an interface Iu. Each radio network sub-system RNS consists of a radio network controller RNC controlling a set of logic elements, known as Node B, by means of an interface Iub. The radio network controllers RNC are connected to each other by an interface Iur. Each Node B serves one or more cells of the network. Finally, each user equipment device UE is connected to one or more Node Bs through a radio interface Uu.

[0003] In the example of Figure 1, the UTRAN network comprises three radio network controllers referenced RNC1, RNC2, and RNC3 and each of these radio network controllers controls two Node Bs. Four user equipment devices UE1, UE2, UE3 and UE4 are connected to these Node Bs.

[0004] The user equipment devices have two modes of operation: an idle mode and a connected mode. During the idle mode, no system resource is specifically allocated to the conveyance of data to and from the user equipment device. The user equipment device is in idle mode for example after it is powered on. In this mode, each user equipment device is identified by a core network identity which may be either the IMSI (International Mobile Subscriber Identity) of the user equipment device (which is transmitted to the core network during the first connection of the user equipment device to the UMTS system) or a TMSI (Temporary Mobile Subscriber Identity) for a circuit switch service or a PTMSI (Packet Temporary Mobile Subscriber Identity) for a packet switch service.

[0005] The user equipment device passes into connected mode when there is a request for making a connection to the system. Thus, as soon as information has to be transmitted to a user equipment device in idle mode, the core network uses the UTRAN network to send a paging message to the user equipment device concerned to ask it to pass into connected mode.

[0006] In connected mode, the user equipment device may take four states known as mobility states:

- Cell_DCH for Cell Dedicated Channel;
- Cell_FACH for Cell Forward Access Channel;
- URA_PCH for UTRAN Registration Area Paging Channel;
- Cell_PCH for Cell Paging Channel.

[0007] These four mobility states are described in detail in the radio access network group technical specification "3GPP TS 25.331 V3.5.0", section 7, pages 30-32 and Appendix B, pages 615-622, updated in December 2000.

[0008] In brief, in the four mobility states of the connected mode, system resources are allocated to the transmission of data in the uplink and/or in the downlink. These radio resources may or may not be shared among several user equipment devices.

[0009] In connected mode, the user equipment devices are identified by a URNTI (UTRAN Radio Network Temporary Identity) allocated by one of the Serving Radio Network Controllers (SRNC). The serving radio network controller of a user equipment device in connected mode corresponds to the radio network controller that is linked with the core network for the connection considered. For example, if we consider in Figure 1 that the user equipment device UE3 transmits data to the core network by passing first of all through the radio network controller RNC2 and then through the radio network controller RNC1, the latter is the serving radio network controller associated with the user equipment device UE3.

[0010] In the event of the failure of one of the radio network controllers leading to a break in the connections Iu between this radio network controller and the core network and the loss of all or part of the data pertaining to the user equipment device, for example the URNTIs, all the user equipment devices having this radio network controller as the serving radio network controller are perceived by the core network as being in the idle mode. It must be noted that, when the defective radio network controller starts working properly again, it also perceives all the user equipment devices as being in idle mode. If the core network tries to set up a connection with these user equipment devices to send them data, the radio network controller will try to establish a connection using their core network identity. Since the user equipment devices are in connected mode, they will be unaware of these attempts to make connection. All these user equipment devices are therefore inaccessible until they themselves make their presence known to the network for example by an updating operation. This period of non-accessibility of the user equipment device may be very lengthy and may last several hours.

[0011] At present, the only solution to this problem lies in sending paging messages by testing all the URNTIs possible in order to connect with all the user equipment devices in connected mode having one of these identities and ask them to make their presence known to the network. This approach is not very satisfactory because it is very costly in terms of system resources (in paging channel PCH) and in time. Indeed, there may be more than 100,000 user equipment devices connected to each radio network controller.

[0012] Thus, it is an aim of the invention to find an approach to limit this period of non-accessibility of user

equipment devices to the utmost possible extent.

[0013] An object of the invention therefore is a user equipment device of a mobile radio telecommunications system, said user equipment device working selectively in two modes of operation, a connected mode in which resources of the system are allocated to setting up a connection with the user equipment device and an idle mode, said user equipment device being identified in idle mode by a first identity and in connected mode by a second identity, characterized in that the user equipment device in connected mode is capable of processing messages in which it is identified by its first identity.

[0014] This characteristic and the advantages of the invention shall appear more clearly from the following detailed description which is made with reference to the appended drawings, of which:

- Figure 1, which has already been described, shows the standard architecture of a UMTS system;
- Figure 2 illustrates the working of a user equipment device according to the invention following a failure of a radio network controller.

[0015] According to the invention, each user equipment device of the system in connected mode is capable of processing the messages in which it is identified by its core network identity.

[0016] Figure 2 considers a user equipment device UE in connected mode linked by radio with a radio network sub-system comprising a radio network controller RNC. This radio network sub-system is linked with the core network CN of the system. In the core network, the user equipment device is identified either by its IMSI or by its TMSI for a circuit switch service, or by a PTMSI for a packet switch service.

[0017] As an alternative embodiment, the user equipment device may be identified in the core network by an identity used in any type of public land mobile network, for example a GSM-MAP network or a DS-41 network.

[0018] At the time t0, the user equipment is perceived by the radio network sub-system RNS and the core network CN as being in connected mode.

[0019] At the time t1, a failure occurs in the radio network controller RNC. This RNC is put back into operation and reinitialized at the time t2. The user equipment device UE is then perceived by the radio network controller RNC and the core network CN as being in idle mode when it is actually in connected mode.

[0020] At the time t3, the core network CN sends a paging message to the UTRAN network to reinitialize a data transmission operation. In this message, the user equipment device is identified by one of its core network identities, namely IMSI, TMSI or PTMSI.

[0021] For the UTRAN network, the user equipment UE is in idle mode. It therefore sends the user equipment device the paging message at the time t4 without converting the core network identity contained in this message into a URNTI.

[0022] According to the invention, the user equipment device UE in connected mode recognizes its core network identity in this message and will therefore process this message. In response to this message, the user equipment device UE will for example send an update message to the UTRAN network to inform it that it is in connected mode.

[0023] Assuming that all or part of the parameters of the connection between the user equipment UE and the core network set up before the failure of the radio network controller RNC have been lost during this failure, the UTRAN network may ask the user equipment device UE to go back into idle mode.

Claims

1. User equipment device of a mobile radio telecommunications system said user equipment device (UE) working selectively in two modes of operation, a. connected mode in which resources of the system are allocated to setting up a connection with the user equipment device and an idle mode, said user equipment device (UE) being identified in idle mode by a first identity (IMSI; TMSI; PTMSI) and in connected mode by a second identity, **characterized in that** the user equipment device (UE) in connected mode is capable of processing messages in which it is identified by its first identity (IMSI; TMSI; PTMSI).
2. User equipment device according to claim 1, **characterized in that** said first identity of the user equipment is the international mobile subscriber identity (IMSI) or a temporary mobile subscriber identity (TMSI) for a circuit switch service or a packet temporary mobile subscriber identity (PTMSI).
3. User equipment device according to claim 1 or 2, **characterized in that** said second identity is a UTRAN network temporary identity (URNTI).
4. User equipment device according to claim 1, **characterized in that** said first identity of the user equipment is an identity applicable in any type of public land mobile network such as GSM-MAP or DS-41.




FIG.1




FIG.2



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 30 1345

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
D,A	"Universal Mobile Telecommunications System (UMTS); RRC Protocol Specification" 3GPP TS 25.331 VERSION 3.5.0 RELEASE 1999, 1 December 2000 (2000-12-01), XP002168551 * page 30 - page 32 * * page 615 - page 622 *	1-3	H04Q7/32
A	WO 99 52317 A (NOKIA TELECOMMUNICATIONS OY ; AHMAVAARA KALLE (FI); VIALEN JUKKA (F) 14 October 1999 (1999-10-14) * abstract * * page 5, line 34 - page 8, line 2 * * figures 1,4,5 *	1	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			H04Q
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 30 May 2001	Examiner Rabe, M
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPC FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 1345

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

30-05-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9952317 A	14-10-1999	FI 980783 A	04-10-1999
		AU 3150299 A	25-10-1999
		BR 9909396 A	05-12-2000
		EP 1068758 A	17-01-2001
